

Home Innovation NGBS GREEN CERTIFIED

Thomas M. Kenney, P.E. - VP Re

THIS IS TO SIGNIFY THAT THE FOLLOWING PRODUCTS FOR RESIDENTIAL CONSTRUCTION

ARCH WOLMANIZED® OUTDOOR® WOOD AND WOLMANIZED ERAWOOD[™] LUMBER

MANUFACTURED BY

ARCH TREATMENT TECHNOLOGIES, INC.

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700 NATIONAL GREEN BUILDING STANDARD AS DETAILED IN NGBS GREEN CERTIFIED PRODUCT REPORT #NGBSGCP-00131.

April 26, 2010

March 31, 2017



Approval Date

Expiration Date

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.

Home Innovation Research Labs | 400 Prince George's Boulevard | Upper Marlboro, MD 20774 | HomeInnovation.com/green

ngineering



NGBS Green Certified Product Report #NGBSGCP-00131

Products: Arch Wolmanized[®] Outdoor[®] Wood and Wolmanized EraWood[™] Lumber

Manufacturer: Arch Treatment Technologies, Inc.

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2008 NATIONAL GREEN BUILDING STANDARD					
PRACTICE #	PRACTICE DESCRIPTION	Potential Points Available	Additional Conditions of Use to Award Points		
2008 NGBS 602.8	Termite-resistant materials are used in portions of the building.	2-6	To earn two points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites.		

2012 NATIONAL GREEN BUILDING STANDARD					
PRACTICE #	PRACTICE DESCRIPTION	Potential Points Available	Additional Conditions of Use to Award Points		
2012 NGBS 602.1.6	Termite-resistant materials are used in portions of the building	2-6	To earn two points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites.		